Coll 50 / 80 / 150

Single-sided butyl adhesive strip
Riwega | eternitycomfort

Technical data sheet
of: 06/02/2014
Art. 02044050 / 02044080 / 02044150
Rev.04 of: 16/08/2021

Properties	Coll 50	Coll 80	Coll 150
Article no.	02044050	02044080	02044150
Material	butyl / LDPE-film		
Liner	PE		
Measurements	50 mm x 15 m	80 mm x 15 m	150 mm x 15 m
Thickness	1 mm	2 mm	1 mm
Colour	Grey		
Weight (DIN EN ISO 1183-1)	approx.1,40 g/cm^3		
Application temperature	+5°C / +30°C		
Service temperature	-40°C / +100°C		
Hardness - Shore00 (DIN EN ISO 868)	approx.40		
Viscosity (DIN EN ISO 7390)	Stable		
Ignition temperature (DIN 51794)	>400°C		
Compression resistance (DTU 39.4)	>0,04 N/mm^2		
Solid content (DIN EN ISO 10563)	>99 %		
Fire behavior (DIN 4102)	B2, normally flammable		
UV-stability	3 months*		
Emissions (Emicode®)	Very low		
Packaging	12 rolls	4 rolls	4 rolls
Storage	Store in a dry place at approximately 20°C, out of direct sunlight for a maximum of 12 months		

*In riferimento al clima dell'Europa Centrale

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.