Coll Fire B 75

Butyl adhesive tapes fire classified
Riwega | eternitycomfort

Technical data sheet
of: 29/11/2019
Art. 02044060
Rev.02 of: 02/12/2024

Properties	
Measurements	75 mm x 10 m
Adhesive	Butyl
Adhesive backing	Aluminium / PET film
Covering material	Silicone liner
Colour	Grey with black aluminum film
Solvents and plasticizers (TVOC test)	30 µg/m³ (ISO 16000-6) compliant with the SINTEF standard
Thickness (without liner)	0,6 mm
Vapour resistance coefficient [µ]	2720000
Tensile strength MD/CD*	185 N/50mm / 200 N/50mm (EN 12311-1)
Elongation at break MD/CD*	10% / 20% (EN 12311-1)
Probe Tack	7.0 N (ASTM D 2979)
Solids	100%
180° Peel Adhesion	27 N/cm (ASTM D 1000)
Fire classification	B-s1, d0 (EN ISO 11925-2, EN 13501-1)
Working temperature	0°C / +40°C
Operating temperature	-30°C / +90°C
UV stability	High**
Packaging	8 rolls
Storage	Cool and dry away from UV rays, max.12 months
Storage temperature	+18°C / +25°C

* MD: longitudinal; CD: transversal
** Referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.