FDB INT VSK PLUS FL

Acrylic adhesive tape with additional adhesive strip/INTERNAL USE
Riwega | eteritycomfort

Technical data sheet
of: 16/05/2022
Art. 02046208 (85 mm) – 02046210 (100 mm)
Rev.00

Characteristic	Method	FDB INT VSK PLUS FL 85	FDB INT VSK PLUS FL 100
Article		02046208	02046210
Adhesive		Modified polyacrylate	
Adhesive support		Combination of PP + PE, with fingerlift	
Liner		White film, precut to 25 mm	
Roll width		85 mm	100 mm
Total weight	EN 1849-2	420 g/m^2 (± 10 g/m^2)	
Roll length		25 m	
Colour		Pink	
Thickness	EN 1849-2	0,49 mm	
Maximum permissible total deformation		5% (in the area of the unconstrained tape width, otherwise an expansion reserve must be provided)	
Tensile strength MD*	EN 12311-1	300 N/50mm	
Tensile strength CD*	EN 12311-1	55 N/50mm	
Elongation MD*	EN 12311-1	25 %	
Elongation CD*	EN 12311-1	135 %	
Sd value	EN 1931 / EN 12572	40 m	
Airtightness	EN 1026	$a_n \leq 0,1$ m^3/m^{2}h	
Resistance to water penetration	EN 13984 / EN 1928	W1 Water column > 2000 mm	
Working temperature		+5°C / +40°C	
Temperature resistance		-40°C / +80°C	
Fire reaction class	EN ISO 11925-2: 2010	Class E	
UV-stability		Do not expose to UV radiation	
Packaging		4 rolls	
Storage		Store in a cool and dry place, in the original package for max. 12 months	

* MD= Machine Direction; CD= Cross Direction

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com. This data sheet replaces the previous copy.