Tape Reflex

Polyethylene adhesive tape with a reflective effect

Riwega | eternitycomfort

Technical data sheet
of 06/02/2014
Art. 02040180
Rev.04 of 11/08/2021

PROPERTIES	
Measurements	80 mm x 25 m
Colour	Alu
Adhesive	Solvent and emollient free acrylic based adhesive
Adhesive backing	Aluminium sprayed PP
Adhesive weight	210 g/m2 (DIN EN ISO 536)
Reinforcement	None
Thickness (without cover)	0,20 - 0,25 mm (DIN EN 1942)
Covering material	Silicone liner
Tear strenght with elasticity	≥ 70 N/25mm; 80% (DIN EN 14410)
Application temperature	+5 °C / +30 °C
Operating temperature	-30 °C / +100 °C
Sd value	Approx. 42 m
Resistance to detachment	Passed (DIN 4108-11)
Resistance to condensation	Very high
Resistance to aging	Very high
Initial adhesion (*tack*)	Very high
UV stability	1 month*
Packaging	6 rolls
Storage	Cool and dry away from UV rays, max. 24 months
Storage temperature	+18 °C / +25 °C

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com. This data sheet replaces the previous copy.